ENSTA 3A – Parcours Robotique & IA : ROB313

Co-design approaches for 3d cameras

ENSTA

D IP PARIS

Antoine MANZANERA – ENSTA-Paris U2IS – Robotics & Computer Vision

Co-design approaches for the perception of 3d using digital cameras

Objectives of this lecture:

- Getting a global view of the bio-inspired and/or co-design opportunistic approaches, making the most of the different parts of a computer vision system (optics / mechanics / electronics / software) to increase its perception and analysis capabilities.
- Understanding the principle of the main categories of codesign approaches for the perception of 3d by a computer vision system.



🚫 IP PARIS

Co-design approaches for the perception of 3d using digital cameras

Outline of this lecture:

Part 1: Bio-inspiration?

- Stereovision and multi-view 3d
- Other 3d cues
- Learning based approaches

Part 2: Active 3d

- * Time of flight
- Structured light

Part 3: Passive 3d

- Plenoptic cameras
- Depth from (de)focus
- Coded aperture





Almost all evolved biological vision systems use two eyes or more.

Stereovision is the main mechanism used by human for 3d sensing.

However, for some animals, the two fields of view do not overlap: differential motion parallax is used instead.

Stereovision and structure from motion are popular techniques for computer vision based 3d reconstruction algorithms.

But many other vision cues are also used by humans for 3d sensing, that may be exploited by future co-design systems.

Those different cues are probably readily used by the learning based (CNN) approaches, though their interpretation is a tricky issue.



VISUAL MATCHING AND 3D PERCEPTION





STEREOVISION AND STRUCTURE FROM MOTION





Knowing the geometry of the first focal plane, i.e. the position of the optical centre (x_c, y_c) , which is the projection of the aperture on the focal plane, and the focal distance *f*, which is the distance of the aperture to the focal plane, the optical path of every point Q₁ projected on the focal plane can be back-traced (back-projection of point Q₁ in blue).

For a camera, these so-called *intrinsic* parameters are estimated by calibration.

STEREOVISION AND STRUCTURE FROM MOTION



🚫 IP PARIS

The same applies for a 2^d focal plane. If Q_1 and Q_2 correspond to the same point (matching) then their back-projections intersect at this point P.

For a camera, if the 2 focal planes belong to 2 distinct cameras (stereovision), then the relative position of the 2 cameras must be estimated by calibration (*extrinsic* parameters).

For 1 single camera, its displacement has to be precisely estimated (*visual odometry*).

STEREOVISION AND STRUCTURE FROM MOTION



DEPTH AND THE BINOCULAR VERGENCE



Triangulation principle:

$$Z = D \frac{\sin \beta}{\sin(\alpha + \beta)}$$
$$Z' = D \frac{\sin \alpha}{\sin(\alpha + \beta)}$$

Vergence angle:

$$\theta = \pi - (\alpha + \beta)$$

$$Z = D \frac{\sin \beta}{\sin \theta}$$
$$Z' = D \frac{\sin \alpha}{\sin \theta}$$



DEPTH AND ACCOMMODATION (MONOCULAR)



🚫 IP PARIS

The accommodation mechanism consists in deforming the eye lens to adjust its focal in such a way that the image of the focalised object appears sharp on the retina.

Short focal: near object appears sharp on the retina plane



DEPTH AND ACCOMMODATION (MONOCULAR)



On the contrary, the points out of the focalisation plane P_f form an image whose level of blur is proportional to their distance to P_f .

See: depth from defocus

(Note the ambiguity of the position due to the blur symmetry with respect to P_f).

Focal too long: near object appears blurred on the retina plane



11 / 82

STEREOPSIS VS 3D DISPLAY

In natural binocular vision (stereopsis), vergence and accommodation are congruent (left diagram).

It is however possible to put – more or less deliberately – in conflict these two functions (right diagram). Thanks to this mechanism, it is possible to get a sharp 3d perception using a 2d display.



ENSTA

🚫 IP PARIS

3D DISPLAY: ANAGLYPHS



Šibenik City Hotel Hall (Anaglyph)



© DNSoft@Panoramio





3D DISPLAY: AUTOSTEREOGRAMS





L.M. Rutherford, Full Moon, stereo pair (1864)

DIP PARIS

3D DISPLAY: PARALLAX BARRIER 3D SCREEN

In parallax 3d-barrier screens, an opaque vertical grid is positioned between the liquid crystal layer and the colour filters (pixels), in such a way to separate by parallax pixels seen by the left eye from those seen by the right one.

Ex: Nintendo 3DS





😥 IP PARIS

[III. howstuffworks.com]



PARALLAX AND THE OPTICAL FLOW



(O,X,Y,Z) 3d real coordinates

(O,x,y) 2d retinal coordinates

Perspective equation (pinhole model):

$$x = \frac{f X}{Z}$$

Time derivative (optical flow):

$$\dot{x} = f\left(\frac{\dot{x}}{Z} - \frac{X\dot{Z}}{Z^2}\right)$$

In the case of a pure translation along OX axis (horizontal travelling, $\dot{Z} = 0$; $\dot{X} = Cte$):



🚫 IP PARIS

Depth is inversely proportional to the magnitude of apparent velocity.

THE FLIGHT OF THE BUMBLEBEE

Roll

Yaw

Lift translation

Roll rotation

evation

(b)

180

Azimuth

Thrust

Pitch

(a)

(c)

(d)



[Jürgen Tautz 2008]

The bee is able to navigate in small corridors by controlling the direction of his flight from the balance of the spatial average apparent speeds estimated by his left and right eyes.



DYNAMIC MONOCULAR 3D: PARALLAX

$$Z = \frac{f \dot{X}}{\dot{x}}$$



[© nvnews.net]





[Kenneth M. Steele 2014]

IP PARIS

STATIC MONOCULAR 3D: OCCLUSIONS



Giotto – Pentecoste (c. 1305)

ENSTA

D IP PARIS

STATIC MONOCULAR 3D: SHADOWS

Self shadowing is a strong but ambiguous depth cue (light source position *vs* concavity).

Without shape prior, the concavity is determined by a prior of top lighting (left image).

When the shape prior is strong (face then convex), the concavity prior dominates the lighting prior (top-down effect, animation on the right).

See shape from shading





STATIC MONOCULAR 3D: SIZES





D IP PARIS

Georges Seurat – Un dimanche après-midi à l'Île de la Grande Jatte (1884-86)

STATIC MONOCULAR 3D: PERSPECTIVE





Stanley Kubrick – The Shining (1980)



3 STATIC MONOCULAR 3D: SIZES AND PERSPECTIVE



Stanley Kubrick – Full Metal Jacket (1987)

ENSTA

PERSPECTIVE: HORIZON AND VANISHING POINT



Stanley Kubrick – Full Metal Jacket (1987)



ENSTA

STATIC MONOCULAR 3D: SIZES VS PERSPECTIVE

Two popular examples of conflict between monocular depth cues:





The Ame's room

STATIC MONOCULAR 3D: SIZES VS PERSPECTIVE





Avignon TGV station: illusory space amplification created by accelerated perspective

STATIC MONOCULAR 3D: TEXTURE GRADIENTS





IP PARIS

TEXTURE GRADIENTS, SIZES AND PERSPECTIVES





Gustave Caillebotte – Rue de Paris, temps de pluie (1877) Antoine MANZANERA – ROB313 : Co-design for 3d

IP PARIS

PERSPECTIVE: HORIZON AND VANISHING POINTS





D IP PARIS



END-TO-END LEARNING OF DEPTH MAPS?



Deep Neural Networks have the capability to exploit all possible 3d cues to predict dense depth maps from videos...

See Next lecture on 3d reconstruction...





Active 3d cameras aim at measuring the depth of every point from the scene that is projected on the image plane, using its response to a particular lighting.

The two fundamental components of the system are then:

- 1. A lighting system controlled in time and space
- 2. A sensing device to analyse the illuminated scene

Such systems are active in that they *emit* a light signal (not to be confused with the other sense of « active vision », i.e. that « moves to see »).



🚫 IP PARIS

ACTIVE APPROACHES AND DIFFUSION MODELS

For 3d active cameras, it is assumed that every point illuminated by the projector in the camera field of view reflects a part of its light toward the optical centre of the camera.

The nature of light diffusion at the measured point then has a major influence in the depth estimation...



Lambertian diffusion

Perfect specular reflection (mirror)

Semi specular diffusion



Note that this may also be an issue for passive approaches (e.g point matching between two poses).

Dip Paris

ACTIVE 3D: "TIME OF FLIGHT" CAMERAS

3d « time of flight » (ToF) cameras measure the distance d_x between a point X projected in x, from the propagation time t_x of light (with speed c) from its emission by the projector until its reception by the photosensor associated to x, after being reflected by point X:

$$d_x = \frac{c.\,t_x}{2}$$

Unlike scanner like (e.g. LIDAR) systems, the light emitted by ToF cameras (usually laser infrared LED) illuminates the whole scene simultaneously.

Different technologies can be used to measure time of flight:

- Direct time measuring (impulsion light)
- Phase estimating (time-modulated continuous light).



ACTIVE 3D: TOF CAMERA BASED ON PHASE ESTIMATION

- The scene is uniformly illuminated with a light whose intensity varies in time according to a sine signal (in red) with amplitude E.
- * The signal received in pixel x (in green) has the same frequence, a weaker amplitude A depending on the reflectivity of the point and a phase shift φ depending on its distance.
- The signal received is also shifted in intensity (offset) of a value B due to the background light present in the scene.
- * This signal is sampled and the phase shift ϕ is deduced from the measured intensities.
- The modulation period λ (typ. 50 ns) is large with respect to the time of flight to avoid phase ambiguities, but small with respect to typical acquisition times to allow repeating the measure (time filtering).



ACTIVE 3D: "STRUCTURED LIGHT" CAMERAS

Structured light 3d cameras interpret the deformation of a 2d image projected into the scene to recover depth information.

They are based on the same triangulation principle as stereovision:

$$R = B \frac{\sin \theta}{\sin(\alpha + \theta)}$$

The structure of projected 2d images determines a spatial coding that plays a major role in triangulation.



3D Object in the Scene

[Geng 2011]




ACTIVE 3D: "STRUCTURED LIGHT" CAMERAS

$$R = B \frac{\sin \theta}{\sin(\alpha + \theta)}$$

The angle α is provided by the position of the point in the image, and the angle θ by the corresponding colour (or pattern) in the reference plane:





ACTIVE 3D: "STRUCTURED LIGHT" CAMERAS

Also:

 $\frac{d}{B} = \frac{Z}{D_{ref} - Z}$

And then:

 $Z \approx \frac{D_{ref}}{B} d$

So, if the projected image is a sinusoidal ramp, depth can be deduced from the phase shift:





🚫 IP PARIS



"STRUCTURED LIGHT" CAMERAS: CALIBRATION



STRUCTURED LIGHT: WHICH PATTERNS?

- Ideally, every point should be uniquely indentified from its value/colour...
 - ...but all the values must be easily distinguishable!
- - ...but then each neighbourhood must be unique!
- Depth being associated to an angle, a 1d target (band) is sufficient...
 - * ...but using a 2d target may solve ambiguities!
- Several targets may also be sequentially combined...
 - ...but then the acquisition time increases!



🚫 IP PARIS

STRUCTURED LIGHT: SEQUENTIAL TARGETS



Binary sequence 2⁵



[Posdamer 1982, from Geng 2011]

Binary targets allow to optimally discriminate the different values.

Depth resolution depends on the number of distinct values and then, for sequential techniques, on the acquisition time.



[from Naramsimhan 2006]



STRUCTURED LIGHT: SEQUENTIAL TARGETS



STRUCTURED LIGHT: UNIQUE "SNAPSHOT" TARGET

- To better distinguish the values, rectangular (runs) targets are preferred to continuous ones (ramps).
- To be able to locally discriminate points using quantised values, local patterns (neighbourhoods) can be used instead of the value alone.
- * But then, each pattern must define a *unique* position.

De Bruijn's sequence B(n,k) are words from a *n*-symbols alphabet such that all the sub-words of length *k* are different.



De Bruijn's sequence B(2,3)





FNSTA

STRUCTURED LIGHT: UNIQUE "SNAPSHOT" TARGET

Using a unique (« snapshot ») target reduces significantly the acquisition time and then allows to acquire mobile scenes:







[Zhang 2002]

DE BRUIJN'S TARGET: SNAPSHOT VS SEQUENTIAL

Targets designed for snapshot acquisition can be used with *phase shifts* for sequential acquisitions, to improve both robustness and resolution (static scenes):





Sequential acquisition: 7 interlaced targets



[Zhang 2002]

« Snapshot » acquisition

IP PARIS

STRUCTURED LIGHT: UNIQUE "SNAPSHOT" TARGET

2d « snapshot » target by pseudo-random patterns generated using a brute-force algorithm:





[Geng 2011]



STRUCTURED LIGHT: UNIQUE "SNAPSHOT" TARGET

The first version of the Kinect[™] includes an RGB camera associated to a structured light 3d camera using a pseudo-random patterned infra-red light.



[Kinect v1 - © Microsoft]







😥 IP PARIS

Part 3: 3D CAMERAS / PASSIVE APPROACHES

For energy and / or discretion purposes, it may be better for an observation system, not to emit light.

The passive techniques get the information using only the light intensity captured by the photosensors.

The approaches presented in this chapter are all based on a non-pinhole aperture associated to a lens, by making the most of the focus and blur information:

- Plenoptic camera
- Depth from (de)focus
- Coded aperture





Plenotic camera 3d Raytrix[™]



Light field plenotic camera Lytro[™]

PASSIVE APPROACHES: PINHOLE...



PASSIVE APPROACHES: ... VS LENS



With a lens on the aperture, each point of the scene illuminates the focal plane along many different optical paths, corresponding to the line beam formed by the cone whose basis is the aperture.

Each path line corresponds to an infinitesimal portion of the aperture, through which the scene is perceived under a particular angle.

Each infinitesimal portion then forms a pinhole-like image, and the image formed by the lens corresponds to the sum of those many « pinhole images ».

If the point is in the conjugate plane of the focal plane (sharpness plane), all the different paths converge on the image, and the point appears sharp, otherwise it appears more or less blurred depending on its distance to the sharpness plane.

→ Depth from (de)focus



ENSTA

PASSIVE APPROACHES: LENS AND APERTURES



IP PARIS

By using an excentric aperture (figure), a sub-set of the optical paths is selected, reducing both the blur and the light intensity.

Points in the sharpness plane (yellow lines) remain at the same location in the image plane.

Closer points (red lines) are deviated in the direction of the aperture.

Further points (green lines) are deviated in the inverse direction.

→ Coded aperture:

Modify the geometry of the aperture for an easier interpretation of the blur (≈ point spread function of the aperture).

→ Plenoptic camera:

Separate physically the different optical paths within subbeams focalised on distinct parts of the sensor.

PASSIVE 3D: PLENOPTIC CAMERA

In a plenoptic camera, the optical paths are separated within sub-beams that are focalised on different parts of the sensor.

(Figure: mini-pinholes, but also 1d lenticular grid, or 2d micro-lens grid).

The captured information is then composed of one macro-image made of many hyper-pixels (or micro-images). (See figure:

- Macro-image of 1x9 hyper-pixels.
- Hyper-pixel of size 1x3.)

The plenoptic image then captures a 4d information: $l(x,y,\xi,\varsigma)$, where (x,y) is the direction of a point illuminating the aperture (light cone), and (ξ,ς) a particular view of this point through the aperture.





🚫 IP PARIS

PLENOPTIC CAMERA: MACRO-IMAGE

[Ng 2005]







PLENOPTIC CAMERA: MICRO-IMAGES



PLENOPTIC CAMERA: MICRO-IMAGES



PLENOPTIC CAMERA: MICRO-IMAGES



PLENOPTIC CAMERA: MACRO-IMAGE



[Ng 2005]



D IP PARIS

PLENOPTIC: MACRO-IMAGE AND DUAL MACRO-IMAGES

Dual macro-images are made by recomposing $m \ge m$ sub-sampled images of size $n \ge n$ from the homologous pixels of all the micro-images, where $n \ge n$ is the number of micro-images (resolution of the macro-image), and $m \ge m$ is the resolution of the micro-image.

Dual macro-images then correspond to a partition of the aperture into distincts viewpoints and then present parallax differences, from which depth information can be deduced by matching (*single-lens stereo*).



GEOMETRY OF THE THIN CONVERGENT LENS



🛞 IP PARIS

RELATION FOCUS / DISTANCE: SHORT FOCAL



RELATION FOCUS / DISTANCE: LONG FOCAL



Estimating the distance can then be made by estimating the blur width in the image.

Without prior on the image focal, a single measure is always ambiguous, the function h(d)being not injective (Figure).



To perform direct measurement of the blur width by image processing, an hypothesis on the structure of the sharp image is necessary: impulsion, step-like contour, in order to predict the effect of blur on this structure.



IP PARIS



🚫 IP PARIS

If the blur is modelled by a 2d Gaussian convolution whose standard deviation depends on h, h can be deduced from the effect of blur on a step-like contour structure, by measuring the local maximum of the gradient value in the direction orthogonal to the step.

Those structures correspond to the classic definition of contours, i.e. the zerocrossings of the second derivative in the gradient direction *g*:

$$C_I = \left\{ x; \frac{\partial^2 I}{\partial g^2}(x) = 0 \right\}$$

Question: how to justify the use of a Gaussian blur model when the geometric optics predicts a gate (square) function?



 $I(x) = (I^{H}(x), I^{S}(x), I^{V}(x))$

 $\frac{\partial I^V}{\partial g}(x)$ (gradient magnitude)











Measuring the gradient magnitude along the contours allows estimating the blur width *h*, but remains ambiguous regarding the position with respect to the sharpness plane.





Mesuring the blur width along the contours



<u>Idea</u>: repeat the measure while varying the aperture ω and/or the image focal *f*?

[Pentland 1987]



The blur width depends linearly of the aperture, then using different apertures only does not disambiguate the distance from the sharpness plane:



distance



Constant focal, variable aperture.





In contrast, using several couples (aperture, image focal) allows to deduce the distance from the blur width in an absolute manner.

(Figure: product $f_i \omega_i$ constant)

[Pentland 1987]



distance



Aperture constant, variable focal.



BLUR MODEL VS APERTURE CALIBRATION

The Gaussian kernel is considered a better blur model than the gate function because the blur is actually the combination of several phenomena: diffraction, chromatic aberrations, discretisation, that lead to the composition of several convolutions.

However a better alternative to blur models is to perform an aperture calibration of the camera by recording the different images formed by one point for different focalisation distances (point spread functions of the convolution kernels).





Traditional 5-blade diaphragm and the family $\{g_d\}_{d\in D}$ of calibrated kernels.

Estimating the right distance is then equivalent to finding the kernel g_d which best corresponds to the local observation.

The « direct » estimation being only possible on contours, indirect estimation is used instead, using deconvolution...





I the observed image

 $\{g_d\}_{d\in D}$ the family of calibrated convolution kernels, indexed by distance

 J_d the deconvolution of I by g_d

The reconstruction error $\varepsilon_d(x)$ at pixel x and distance d is defined as:

$$\varepsilon_d(x) = \sum_{y \in W_x} \|I - J_d \star g_d\|^2$$

where W_x is a spatial neighbourhood of x.

Distance estimation is then performed as follows:

$$d_{opt}(x) = \arg\min_{d\in D} \varepsilon_d(x)$$



🔎 IP PARIS

DECONVOLUTION: INVERSE AND WIENER FILTERING

The problem is now equivalent to image deconvolution (restoration), the convolution kernel at the origin of the blur being known (non-blind).

Quick sketch of non-blind deconvolution:

 $F = I \star g_d \xrightarrow{Fourier} \widetilde{F} = \widetilde{I} \times \widetilde{g_d} \xrightarrow{Inverse filter} \widetilde{J_d} = \frac{\widetilde{F}}{\widetilde{g_d}} \xrightarrow{Inverse} J_d$

Not usable because of the zeros of $\widetilde{g_d}$ and additive noise!!!

$$F = I \star g_d + b \xrightarrow{Fourier} \widetilde{F} = \widetilde{I} \times \widetilde{g_d} + \widetilde{b} \xrightarrow{Wiener \ filter} \widetilde{J_d} = \frac{\widetilde{g_d}' \times \widetilde{F}}{\widetilde{g_d}\widetilde{g_d}' + \alpha} \xrightarrow{Inverse} J_d$$



🚫 IP PARIS

 α is a regularisation term, which depends on the relative power of noise *b* with respect to image signal *I*. It can be set as constant or depend on frequencies: $\alpha(u)$. Wiener filtering thus performs a trade-off between deconvolution and regularisation.

In any case, the reconstruction error ε_d strongly depends on the zeros of the convolution filter in the frequency domain ($\widetilde{g_d}$).

DECONVOLUTION: INVERSE AND WIENER FILTERING



Left: a (constant speed) motion blur in the frequency domain (cardinal sine), and the corresponding inverse filter.

Right: the same default and the correcting Wiener filters for two different values of α assumed constant.

[Figure: Maître 2003]



🚫 IP PARIS
PASSIVE 3D: CODED APERTURE

In deconvolution techniques, the zeros of the filter in the frequency domain are those that mainly contribute to the reconstruction errors.

As a consequence, if the different convolution kernel candidates $\{g_d\}_{d\in D}$ have their zeros located at the same frequencies in the Fourier domain, it is much more difficult to distinguish their effects on the image (by deconvolution) than if their zeros appear at different locations.

The principle of coded aperture is to choose the shape of the aperture in such a way that the zeros of the different filters $\{g_d\}_{d \in D}$ appear, depending on *d*, at different location of the frequency domain:



PASSIVE 3D: CODED APERTURE







Traditional 5-blade diaphragm and the family $\{g_d\}_{d \in D}$ of kernels.



Coded aperture and the family $\{g_d\}_{d\in D}$ of kernels.

Comparing the kernels in frequency domain $\{\widetilde{g_d}\}_{d \in D}$ between classic and coded apertures (note the location of the zeros):



[Levin 2007]



Conventional aperture Antoine MANZANERA – ROB313 : Co-design for 3d



Coded aperture

74 / 82



PASSIVE 3D: CODED APERTURE

Images obtained by deconvolution with coded aperture allow to better discriminate the right scales (distances):





Antoine MANZANERA – ROB313 : Co-design for 3d

RANGE TEST IMAGE





[Levin 2007]

Antoine MANZANERA – ROB313 : Co-design for 3d

RANGE IMAGE: CODED APERTURE RAW RESULT



IP PARIS

Antoine MANZANERA – ROB313 : Co-design for 3d

77 / 82

RANGE IMAGE: RESULT AFTER POST-PROCESSING



CO-DESIGN FOR 3D: CONCLUSIONS

Co-design techniques aim at globally optimising a vision system by an opportunistic approach which makes the most of the different components and tries to combine them in a more intimate way: optics, mechanics, electronics, digital processing...

This lecture focused on 3d perception, but camera co-design is also much investigated for improving or "augmenting" digital images ("computational photography").

An important feature of co-designed system is the balance between, on the one hand, hardware complexity and intrusive nature (lighting) of the system, and on the other hand, the software complexity. However, the weight of the software remains strong in most of the presented systems.

Another important point about passive systems, is the difficulty (if not impossibility) to process regions without structures (homogeneous).

The principles of the presented techniques are generally old, but the corresponding technology maturation is very recent, with several off-the-shelf products available now.

Finally, many depth visual cues remain unexploited today: there is still plenty of research and development works needed to contribute to the on-going expansion of co-design.



REFERENCES (Part 1)

[Giese 2006] Martin A. Giese, Visual perception, lecture material, University of Tübingen, 2006.

[Tautz 2008] Jürgen Tautz, The Buzz about Bees: Biology of a Superorganism, Springer, 2008.

[Krapp et Wicklein 2008] H.G. Krapp, M. Wicklein *Central processing of visual information in insects*. In: The Senses: A Comprehensive Reference, ed. by A. Basbaum, A. Kaneko, G.M. Shepherd, G. Westheimer, Academic Press, 2008, p. 131–204.

[Hoffman 2008] D.M. Hoffman, A.R. Girshick, Kurt Akeley, M.S. Banks, Vergenceaccommodation conflicts hinder visual performance and cause visual fatigue, Journal of Vision, 2008 vol. 8 no. 3 article 33.

[Steele 2014] Kenneth M. Steele, *Psychology of Perception*, Lecture material, Appalachian State University, Fall 2014 <u>http://www1.appstate.edu/~kms/</u>



🚫 IP PARIS

REFERENCES (Part 2)

[Chiabrando 2009] F. Chiabrando, R. Chiabrando, D. Piatti, F. Rinaudo, Sensors for 3D Imaging: Metric Evaluation and Calibration of a CCD/CMOS Time-of-Flight Camera, Sensors, vol. 9, 10080-10096, 2009.

[Geng 2011] Jason Geng, Structured-light 3D surface imaging: a tutorial, Advances in Optics and Photonics, vol. 3, 128-160, 2011.

[Posdamer 1982] J. L. Posdamer and M. D. Altschuler, *Surface measurement by space-encoded projected beam systems*, Comput. Graph. Image Processing 18, (1), 1–17 1982.

[Narasimhan 2006] S. Narasimhan, *Computer Vision: Spring 2006, lecture n.17*, Carnegie Mellon University.

[Zhang 2002] L. Zhang, B. Curless, S. M. Seitz, *Rapid shape acquisition using color structured light and multi-pass dynamic programming*, IEEE Int. Symp. on 3D Data Processing Visualization and Transmission, pp. 24–36, 2002.



🚫 IP PARIS

REFERENCES (Part 3)

[Adelson 1992] E. H. Adelson, J. Y. A. Wang, Single Lens Stereo with a Plenoptic Camera, IEEE Trans. Pattern Analysis and Machine Intelligence 14(2): 99-106, 1992.

[Ng 2005] R. Ng, M. Levoy, M. Bredif, G. Duval, M. Horowitz, and P. Hanrahan. *Light Field Photography with a Hand-Held Plenoptic Camera,* Stanford University Computer Science Tech Report CSTR 2005-02, April 2005.

[Pentland 1987] Alex P. Pentland, A new sense for depth of field, IEEE Trans. Pattern Analysis and Machine Intelligence 9(4): 523-531, 1987.

[Maître 2003] Henri Maître (ss la direction de), Le Traitement des Images, Chapitre 5 : Restauration, Hermès – Lavoisier, Série I2C, 2003.

[Levin 2007] A. Levin, R. Fergus, F. Durand, W.T. Freeman, *Image and depth from a conventional camera with a coded aperture,* ACM Transactions on Graphics 26 (3): 70-78, 2007.



🚫 IP PARIS